

# Micro Signal Type Tester

## II. STA993X Series Low Noise Precision Power Supply

NEW

### Features

- 7-inch capacitive touch screen with 800 x 480 resolution
- Linux operating system, Chinese and English interface
- Four-quadrant precision power output
- Single/dual channel output and measurement
- Up to  $\pm 210V$  DC voltage,  $\pm 3A$  DC current/ $\pm 10.5A$  pulse
- 10fA/0.1 $\mu$ V minimum output resolution (6 1/2 bits)
- 1pA/10 $\mu$ V minimum measurement resolution (4 1/2 bits)
- Supports voltage, current, resistance, and power measurements
- Four basic modes of voltage source, current source, voltmeter, and ammeter
- Minimum sampling interval 1 $\mu$ s
- Supports DC, pulse, scanning and list outputs
- Pulse output with a minimum pulse width of 50  $\mu$ s
- 1mHz-10kHz arbitrary waveform generation and list scan function (minimum 1 $\mu$ s interval)
- Flexible programmable output resistance function
- Math operation function, sliding average filter function, deviation deduction function
- 14-speed sorting function with Grading and Sorting modes



RS232 standard	LAN standard	HANDER standard	USB HOST standard	USB DEVICE standard
-------------------	-----------------	--------------------	----------------------	------------------------

### STA993X Series

Shelf volume (mm): 235x132x490  
Outline volume (mm): 250x154x530  
Net weight: about 8.5kg (single channel) / 10kg (dual channel)

### Applications

- Analog-to-digital converters and digital-to-analog converters
- High-precision analog ICs and circuits
- RF integrated circuits and circuits
- Medical Applications
- Cable/Harness Evaluation
- Voltage Controlled Oscillator (VCO)
- Sensor devices and transducers

- Solar cells and interface circuits
- Electrochemical applications
- Research & Education
- Crystal Oscillators
- Current source for small voltage measurements
- Battery Management Simulator
- Advanced Materials Evaluation

### Specifications

Product Model		STA9931		STA9932				
Display								
Monitor		7-inch capacitive touch color LCD monitor with 800 x 480 resolution						
Key Indicator								
Channels		1		2				
Max Output	Voltage		$\pm 210V$					
	Current	DC	$\pm 3.03A$					
		Pulse	$\pm 10.5A$					
Power Supply	Max Bits		Bits 6 1/2					
	Min. Resolution	Voltage	0.1 $\mu$ V					
		Current	0.01pA					
Measurement	Max Bits		Bits 4 1/2					
	Min. Resolution	Voltage	10 $\mu$ V					
		Current	1pA					
Voltage Range			0.2V-200V					
Min. Interval Time			1 $\mu$ s					
Voltage Output								
Range	Programming Resolution	Accuracy $\pm$ (% of reading + bias)	DC output voltage or pulse peak/base voltage		Max. Current <sup>1</sup> DC Output      Pulse Output			
					Pulse Width <sup>2</sup>			

# Micro Signal Type Tester

## II. STA993X Series Low Noise Precision Power Supply

0.2V	100nV	$\pm(0.015\%+225\mu V)$	$0 \leq  V  \leq 0.21V$	$\pm 3.03A$	$\pm 3.03A$	$50\mu s \leq t \leq t_{max}$
2V	1μV	$\pm(0.015\%+225\mu V)$	$0 \leq  V  \leq 2.1V$		$\pm 10.5A$	$50\mu s \leq t \leq 1ms$
20V	10μV	$\pm(0.015\%+5mV)$	$0 \leq  V  \leq 6V$	$\pm 3.03A$	$50\mu s \leq t \leq t_{max}$	$50\mu s \leq t \leq 1ms$
			$0 \leq  V  \leq 21V$	$\pm 1.515A$	$\pm 1.515A$	$50\mu s \leq t \leq t_{max}$
200V	100μV	$\pm(0.015\%+50mV)$	$0 \leq  V  \leq 6V$	$\pm 3.03A$	$\pm 3.03A$	$50\mu s \leq t \leq t_{max}$
			$0 \leq  V  \leq 21V$	$\pm 1.515A$	$\pm 1.515A$	$50\mu s \leq t \leq t_{max}$
			$0 \leq  V  \leq 180V$	—	$\pm 1.05A$	$50\mu s \leq t \leq 10ms$
			$0 \leq  V  \leq 200V$	—	$\pm 1.515A$	$50\mu s \leq t \leq 2.5ms$
			$0 \leq  V  \leq 210V$	$\pm 105mA$	$\pm 105mA$	$50\mu s \leq t \leq t_{max}$

**Note:**

superscript<sup>1</sup>: Refer to the Limits table section when using channels 1 and 2 for DC outputs or pulsed outputs ( $50\mu s \leq t \leq t_{max}$  (= 99.9999ks)).

superscript<sup>2</sup>: For pulses with  $50\mu s \leq t \leq t_{max}$ , the maximum duty cycle is 99.9999%.

For pulses with  $50\mu s \leq t \leq 1ms$ ,  $50\mu s \leq t \leq 2.5ms$  or  $50\mu s \leq t \leq 10ms$ , the maximum duty cycle is 2.5%.

Current Output						
Range	Setting Resolution	Accuracy $\pm$ (%) of reading + bias)	DC output current or pulse peak/base current <sup>1,2</sup>	Max. Voltage		Pulse Width <sup>3</sup>
				DC Output	Pulse Output	
10nA	10fA	$\pm(0.10\%+50pA)$	$0 \leq  I  \leq 10.5nA$	$\pm 210V$	$\pm 210V$	$50\mu s \leq t \leq t_{max}$
100nA	100fA	$\pm(0.06\%+100pA)$	$0 \leq  I  \leq 105nA$			
1μA	1pA	$\pm(0.025\%+500pA)$	$0 \leq  I  \leq 1.05\mu A$			
10μA	10pA	$\pm(0.025\%+1.5nA)$	$0 \leq  I  \leq 10.5\mu A$			
100μA	100pA	$\pm(0.02\%+25nA)$	$0 \leq  I  \leq 105\mu A$			
1mA	1nA	$\pm(0.02\%+200nA)$	$0 \leq  I  \leq 1.05mA$			
10mA	10nA	$\pm(0.02\%+2.5\mu A)$	$0 \leq  I  \leq 10.5mA$			
100mA	100nA	$\pm(0.02\%+20\mu A)$	$0 \leq  I  \leq 105mA$			
1A	$1\mu A$	$\pm(0.03\%+1.5mA)$	$0 \leq  I  \leq 105mA$	$\pm 210V$	$\pm 210V$	$50\mu s \leq t \leq t_{max}$
			$105mA \leq  I  \leq 1.05A$		$\pm 21V$	$\pm 21V$
			$0 \leq  I  \leq 1.05A$		—	$\pm 200V$
1.5A	$1\mu A$	$\pm(0.05\%+3.5mA)$	$0 \leq  I  \leq 105mA$	$\pm 210V$	$\pm 210V$	$50\mu s \leq t \leq t_{max}$
			$105mA \leq  I  \leq 1.515A$		$\pm 21V$	$\pm 21V$
			$0 \leq  I  \leq 1.515A$		—	$\pm 200V$
			$0 \leq  I  \leq 1.05A$		—	$\pm 180V$
3A	$10\mu A$	$\pm(0.4\%+7mA)$	$0 \leq  I  \leq 105mA$	$\pm 210V$	$\pm 210V$	$50\mu s \leq t \leq t_{max}$
			$105mA \leq  I  \leq 1.515A$		$\pm 21V$	$\pm 21V$
			$1.515A \leq  I  \leq 3.03A$		$\pm 6V$	$\pm 6V$
10A <sup>4</sup>	$10\mu A$	$\pm(0.4\%+25mA)$ <sup>5</sup>	$0 \leq  I  \leq 10.5A$	$\pm 210V$	$\pm 6V$	$50\mu s \leq t \leq 1ms$
			$0 \leq  I  \leq 1.515A$		—	$\pm 200V$
			$0 \leq  I  \leq 1.05A$		—	$\pm 180V$

\*Note:

superscript<sup>1</sup>: Refer to the Limits table section when using channels 1 and 2 for DC outputs or pulsed outputs ( $50\mu s \leq t \leq t_{max}$  (= 99.9999ks)).

superscript<sup>2</sup>: The maximum base current is 500mA for pulses with  $50\mu s \leq t \leq 1ms$ , and the maximum base current is 50mA for pulses with  $50\mu s \leq t \leq 2.5ms$  or  $50\mu s \leq t \leq 10ms$ .

superscript<sup>3</sup>: The maximum duty cycle is 99.9999% for pulses with  $50\mu s \leq t \leq t_{max}$  and the maximum duty cycle is 2.5% for pulses with  $50\mu s \leq t \leq 1ms$ ,  $50\mu s \leq t \leq 2.5ms$  or  $50\mu s \leq t \leq 10ms$ .

superscript<sup>4</sup>: 10A range for pulse mode only, not for DC mode.

superscript<sup>5</sup>: Measurement speed is 0.01 PLC.

# Micro Signal Type Tester

## II. STA993X Series Low Noise Precision Power Supply

Voltage Measurement				
Range	Voltage Measurement	Resolution	Accuracy	
0.2V	0≤ V ≤0.212V	10µV	±(0.015% + 225µV)	
2V	0≤ V ≤2.12V	100µV	±(0.02% + 350µV)	
20V	0≤ V ≤21.2V	1mV	±(0.015% + 5mV)	
200V	0≤ V ≤212V	10mV	±(0.015% + 50mV)	
Current Measurement				
Range	Current Measurement	Resolution	Accuracy	
10nA	0≤ I ≤10.6nA	1pA	±(0.10 % + 50pA)	
100nA	0≤ I ≤106nA	10pA	±(0.06% + 100pA)	
1µA	0≤ I ≤1.06µA	100pA	±(0.025% + 500pA)	
10µA	0≤ I ≤10.6µA	1nA	±(0.025% + 1.5nA)	
100µA	0≤ I ≤106µA	10nA	±(0.02% + 25nA)	
1mA	0≤ I ≤1.06mA	100nA	±(0.02% + 200nA)	
10mA	0≤ I ≤10.6mA	1µA	±(0.02% + 2.5µA)	
100mA	0≤ I ≤106mA	10µA	±(0.02% + 20µA)	
1A	0≤ I ≤1.06A	100µA	±(0.03% + 1.5mA)	
1.5A	0≤ I ≤1.53A		±(0.05% + 3.5mA)	
3A	0≤ I ≤3.06A	1mA	±(0.4% + 7mA)	
10A <sup>1</sup>	0≤ I ≤10.6A		±(0.4% + 25mA)	
<b>*Note:</b> superscript1 For pulse mode, not for DC mode.				
Pulse source (pulse width is the time from 10% rising edge to 90% falling edge, base level: pulse low level, peak level: pulse high level)				
Minimum programmable pulse width	50µs			
Pulse width programming resolution	1µs			
Interface	RS232C、MSB HOST、MSB DEVICE、LAN、HANDLER			
Environment & Temperature				
Environment	Suitable for indoor equipment			
Temperature of operating condition	0°C - 55°C			
Humidity of operating condition	30% - 80% RH (non-condensing)			
Elevation of operating condition	0 - 2000m (6561ft)			
Temperature of storage condition	30°C - +70°C			
Humidity of storage condition	10% - 90% RH (non-condensing)			
Elevation of storage condition	0 - 4600m (15092ft)			
Warm-up time after power on	≥60minutes			
General Indicator				
Power supply	90 V to 264V, 47 Hz to 63Hz, maximum			
Power consumption	< 250VA			
Rack mount	215mmx132mmx490mm			
Dimension	235mmx154mmx530mm			
Weight	Approx. 8.5kg (single)/10kg (dual)			
Safety	Class I Safety			
EMC standards	IEC61326-1/EN61326-1			
AS/NZS	CISPR 11			
Insulation resistance	Under the reference working conditions, the insulation resistance between the power terminals and the shell is not less than 50MΩ; Under humid and hot transportation conditions, the insulation resistance between the power terminals and the shell is not less than 2MΩ.			
Dielectric strength	Under the reference working conditions, the power terminals and the shell can withstand the rated voltage of 1.5kV, frequency of 50Hz AC voltage for 1 minute, without breakdown and flying arc phenomenon.			
Leakage current	≤3.5mA			
Safety certification	CE、cCSAµs、C-Tick			

### Standard Accessories

Three-core power cord

SBF0050B Test cable at both ends

STA9931-003 Ultra Low Noise Filter

SBF0017 USB Device connection cable

SBF0050C Four-terminal test cable